

**AMENDMENTS TO THE CLAIMS**

---

1. (Currently Amended) An ink jet printing method which comprises:  
directly forming an image on a printing medium on the basis of signals of image data;  
and  
fixing the image by heating to produce a printed matter,  
wherein:  
said image formation is carried out by an ink jet system of ejecting an oily ink by an  
electrostatic field;  
said image formation on the printing medium is carried out by sequentially using two or  
more inks; and  
each of said inks comprises at least a coloring material and a disperse particulate resin  
component.

2. (Withdrawn) The ink jet printing method according to claim 1, further comprising  
cleaning an ink jet head, said cleaning step comprising:  
immersing said ink jet head in a cleaning solution; and  
applying voltage to said ink jet head.

3. (Original) The ink jet printing method according to claim 1, further comprising, when  
a malfunction happens, either or both of stopping the image formation and eliminating a cause of  
the malfunction.

4. (Withdrawn) The ink jet printing method according to claim 3, wherein at least one of  
the following steps is performed:  
removing dusts on the surface of said printing medium either of both of before and during  
printing onto said printing medium; and  
cleaning said ink jet head at least after printing is finished.

5. (Withdrawn) The ink jet printing method according to claim 1, wherein said oily ink is a dispersion comprising at least:

a nonaqueous solvent having an intrinsic electrical resistance of  $10^9 \Omega \cdot \text{cm}$  or more and a dielectric constant of 3.5 or less; and  
colored particles dispersed in said solvent.

6. (Currently Amended) An ink jet printing apparatus comprising:

an image-forming member which directly forms an image on a printing medium on the basis of signals of image data; and

an image-fixing member for fixing the formed image to obtain a printed matter, comprising a heating member,

wherein:

said image-forming member comprises an ink jet imaging unit comprising at least two ink jet heads for ejecting at least a first and a second oily ink, respectively, which may be the same or different by an electrostatic field;

formation of said image on the printing medium is carried out by sequentially using two or more inks; and

each of said inks comprises at least a coloring material and a disperse particulate resin component.

7. (Withdrawn) The ink jet printing apparatus according to claim 6, further comprising a cleaning member which cleans said ink jet head.

8. (Withdrawn) The ink jet printing apparatus according to claim 7, wherein said cleaning member performs cleaning by applying voltage to the ink jet head which is immersed in a cleaning solution.

9. (Original) The ink jet printing apparatus according to claim 6, further comprising at least one of a malfunction detecting member and a malfunctioning cause eliminating member, wherein according to an output from said malfunction detecting member, the image formation is temporarily stopped or said malfunctioning cause eliminating member operates.

10. (Original) The ink jet printing apparatus according to claim 9, wherein said malfunction detecting member is a unit which detects adhesion of a foreign matter on said ink jet head.

11. (Withdrawn) The ink jet printing apparatus according to claim 9, wherein said malfunction detecting member is a unit which detects at least one of a dust in said ink jet printing apparatus and a dust on said printing medium.

12. (Withdrawn) The ink jet printing apparatus according to claim 9, wherein said malfunction detecting member detects vibration of at least one of said ink jet printing apparatus and said ink jet head.

13. (Withdrawn) The ink jet printing apparatus according to claim 6, wherein said oily ink is a dispersion comprising at least:

a nonaqueous solvent having an intrinsic electrical resistance of  $10^9 \Omega \cdot \text{cm}$  or more and a dielectric constant of 3.5 or less; and  
colored particles dispersed in said solvent.

14. (Withdrawn) The ink jet printing apparatus according to claim 6, further comprising a dust-removing member which removes a dust on the surface of said printing medium either or both of before and during printing on the printing medium.

15. (Withdrawn) The ink jet printing apparatus according to claim 6, further comprising a counter drum which is arranged at a position opposed to said ink jet head via said printing medium and is rotatable so as to move said printing medium upon the image formation.

16. (Withdrawn) The ink jet printing apparatus according to claim 15, wherein said ink jet head has a single channel head or multi-channel head and is movable in an axis direction of said counter drum.

17. (Withdrawn) The ink jet printing apparatus according to claim 6, further comprising at least one pair of capstan rollers for conveying said printing medium upon the image formation with being put therebetween.

18. (Withdrawn) The ink jet printing apparatus according to claim 17, wherein said ink jet head has a single channel head or multi-channel head and is movable in an orthogonal direction to said conveyance direction of the printing medium.

19. (Withdrawn) The ink jet printing apparatus according to claim 15 or 17, wherein said ink jet head has a full line head having a length substantially the same as the width of said printing medium.

20. (Withdrawn) The ink jet printing apparatus according to claim 6, wherein said ink jet imaging unit further comprises an ink feeding member which feeds said oily ink to said ink jet head.

21. (Withdrawn) The ink jet printing apparatus according to claim 20, wherein said ink jet imaging unit further comprises an ink recovering member which recovers said oily ink from said ink jet head to circulate said oily ink.

22. (Withdrawn) The ink jet printing apparatus according to claim 6, wherein said ink jet imaging unit further comprising an ink tank for storing said oily ink and a stirring member which stirs said oily ink in said ink tank.

23. (Withdrawn) The ink jet printing apparatus according to claim 6, wherein said ink jet imaging unit further comprises an ink temperature controller for controlling the temperature of said oily ink in the ink tank.

24. (Withdrawn) The ink jet printing apparatus according to claim 6, wherein said ink jet imaging unit further comprises an ink concentration controller for controlling the concentration of said oily ink.